

İletişim bilgileri : Hexel Endüstriyel Sanayi ve Ticaret A.Ş. / ASO 2. ve 3. OSB Alıcı Mah. 2024.

Caddesi No: 19 Sincan/ANKARA

GALAXY M MODEL TİCARİ ISI POMPASI ÜRÜN BİLGİ FORMU

FEATURE	UNIT	GALAXY M 75	GALAXY M 140
Acoustics			
Lw	dB(A)	86	92
A35/W12-7			
P _c (Cooling capacity)	kW	70	130
EER (Energy Efficiency Ratio)		2.61	2.6
D _{pc} Indoor (Indoor side water pressure drop)	kPa	65	65
SEER AC			
SEER (Seasonal Energy Efficiency Ratio)		5	4.8
η _{sc} (Seasonal space cooling energy efficiency)	%	197	190
A7/W40-45			
P _h (Heating capacity)	kW	75	140
COP (Coefficient of Performance)		3.4	3.13
D _{ph} Indoor (Indoor side water pressure drop)	kPa	74.49	75.54
A7/W30-35			
P _h (Heating capacity)	kW	77	142
COP (Coefficient of Performance)		3.9	3.72
D _{ph} Indoor (Indoor side water pressure drop)	kPa	78.33	77.64
P _{sbc}			
P _{sbc} (Standby mode power input in cooling)	W	80	140
P _{sbh}			
P _{sbh} (Standby mode power input in heating)	W	80	140
SCOP Average W35			
P _{designh} (Design heating load)	kW	48	95
SCOP (Seasonal Coefficient of Performance)		4.5	4.25
η _{sh} (Seasonal space heating energy efficiency)	%	177	167
General			
Refrigerant		R32	R32
Indoor Heat Exc. Type		Plate	Plate
Compressor Details			
Unit Capacity Control (Capacity control type of the unit (EN 14825))		Variable	Variable
Type (Type of the compressor(s))		Scroll	Scroll
Inverter (Inverter (True/False))		true	true
Number (Number of compressors)		1	2